

Diesel Generator Sales, Installation, Hire, Spares, Service & Refurbishment



Certificate No: 1152

YK8SPEC Acoustically Enclosed Generator



GENERAL

OUTPUT RATINGS

50Hz, 230VOLT, SINGLE PHASE

YK8SP 8KVA, 6.4KW

ENGINE KUBOTA Z602 ES

ALTERNATOR MECC-ALTE



TECHNICAL DATA					
Engine Model	Z602	3000RPM			
Cylinders	2	Fuel consumption @100%	2.90		
Cubic Capacity	1.1 Litres	Fuel Consumption @75%	2.3		
Aspiration	Natural	DC system	12V		
Cooling	Water Cooled	Noise Level	67dBA @ 7 metre		
Fuel Tank Capacity	37 Litres	Cooling	Water Cooled - Rad		

These ratings are suitable for continuous output at varying load. No overload available on these ratings. Ratings at 0.8pf for 3 Phase, 1.0pf for 1 phase

SOCKETS:

1 x 115V 16A sockets

2 x 115V 32A socket

2 x 230V 16A sockets

1 x 230V 32A socket

CONTROL PANEL:

Key start / stop, low oil, high engine temperature, and low battery warning lights. MCB / RCD (230v) Hours run meter. Fuel gauge. Emergency stop switch

DIMENSIONS AND WEIGHTS						
Length	Width	Height	Weight inc Lube Oil	Weight inc Lube Oil &		
Mm	Mm	Mm	Kg	Coolant		
1285	655	900	295	320		

Registered Office: Yorpower Limited Electricity Building Blenheim Road Pocklington Industrial Estate York, YO42 1NR UNITED KINGDOM



T: +44 (0) 1759 305400 F: +44 (0) 1759 305405

E: sales@yorpower.com W: www.yorpower.com